## **Amendments to the Claims**

This listing of claims will replace all prior versions, and listings, of claims in the application.

## <u>Listing of claims:</u>

Claims 1-11 (canceled without prejudice or disclaimer)

Claim 12. (new) A hand-operated tool having a user side, comprising a handle portion which is positioned on the user side and which has a bottom side, a foot portion positioned on the bottom side of the handle portion, and a detachable one-piece upper handle shell that is positioned to cover at least substantially the handle portion on the user side and the foot portion on the bottom side.

Claim 13. (new) The hand-operated tool according to claim 12, characterized in that the foot position comprises a reinforcement profile arranged on the bottom side.

Claim 14. (new) The hand-operated tool according to claim 12, which further comprises an inner handle wall injection-molded in one piece and running around an opening in the handle portion.

Claim 15. (new) The hand-operated tool according to claim 14, characterized in that the upper handle shell comprises a functional element arranged on the user side.

Claim 16. (new) The hand-operated tool according to claim 15, wherein the functional element comprises an eyelet.

Claim 17. (new) The hand-operated tool according to claim 14, which further comprises a larger tank half shell, wherein the inner handle wall and the larger tank half shell are formed by being injection-molded in one piece, and which further comprises a

First Preliminary Amendment December 11, 2003 Page 3 of 5

smaller tank shell that is welded to the larger tank half shell along a seam running adjacent to the handle so as to form a fuel tank.

Claim 18. (new) The hand-operated tool according to claim 12, characterized in that the foot portion comprises a dovetail guide running in the longitudinal direction of the tool and that the upper handle shell comprises wrap-arounds arranged on the outseide of the upper handle shell with which the upper handle shell can be shifted in the direction away from the user toward the tool.

Claim 19. (new) The hand-operated tool according to claim 12, characterized in that the upper handle shell comprises a first fastening means in the foot portion and/or a second fastening means in the handle portion.

Claim 20. (new) The hand-operated tool according to claim 19, characterized in that the first fastening means comprises recesses in order to form a snap connection with snap hooks projecting from the bottom of the foot portion.

Claim 21. (new) The hand-operated tool according to claim 19, characterized in that the foot portion comprises screw domes projecting from its bottom and that the first fastening means comprises penetration areas in the upper handle shell for screws that can be screwed into the screw domes for fixing the upper handle shell to the tool.

Claim 22. (new) The hand-operated tool according to claim 19, characterized in that the second fastening means comprises a borehole arranged on the user side for a screw, and two noses arranged on the end of the tool side at an angle to the operative direction of the screw.

First Preliminary Amendment December 11, 2003 Page 4 of 5

Claim 23. (new) The hand-operated tool according to claim 14, characterized in that the handle portion is hollow in order to receive a switching mechanism, that the inner handle wall comprises a recess for a gas lever and that the upper handle shell comprises a recess for a locking key.